



DOOR NUMBER
USE AB-SCHEDULES FOR DOOR & FRAME

RAILING TYPE (SEE A7 SECTIONS FOR DETAILS)

HATCH NOTATIONS: INSULATION
REFER TO DETAIL C24A6-02 OR C24A6-03
REFER TO PLANS AND SECTIONS FOR DETAILS

HATCH NOTATIONS: INSULATION
REFER TO DETAIL C24A6-02, C24A6-03
REFER TO PLANS AND SECTIONS FOR DETAILS

HATCH NOTATIONS: SUSPENDED ACCELS
REFER TO DETAIL AC24A6-02, AC24A6-03
REFER TO PLANS AND SECTIONS FOR DETAILS

HATCH NOTATIONS: ACCELS CEILING
REFER TO DETAIL AC24A6-02, AC24A6-03
REFER TO PLANS AND SECTIONS FOR DETAILS

HATCH NOTATIONS: HORIZONTAL FIBER REINFORCED CONCRETE
REFER TO DETAIL C24A6-02, C24A6-03
REFER TO PLANS AND SECTIONS FOR DETAILS

HATCH NOTATIONS: FLOOR FINISHED WALL
REFER TO PROPERTY STANDARDS
REFER TO PLANS FOR EXTENT

UNIT TYPE
LMP

LMP = SUITE LEGAL NUMBER
MUNIP = MUNICIPAL NUMBER

BARRIER FREE SUITE

5. REFER TO SECTION DESIGN DRAWINGS FOR INTERIOR FINISHES.
6. BALCONY SLABS AND CONCRETE SLAB CONDITIONS TO BE MAINTAINED AS SHOWN ON DRAWINGS. PROVIDE FLOOR FINISHES FOR BALCONIES AND TERRAZAS TO MATCH INTERIOR FINISHES. PROVIDE FLOOR FINISHES FOR TERRAZAS TO MATCH INTERIOR FINISHES.
7. PROVIDE APPROVED SOLID INSULATION FOR HORIZONTAL ROOFING AND VERTICAL WALLS. PROVIDE APPROVED VAPOR BARRIER. REFER TO MECHANICAL DRAWINGS FOR VENTILATION REQUIREMENTS.
8. REFER TO WINDOW SCHEDULE FOR LOCATION OF WINDOWS AND DOORS.
9. PROVIDE ALL FLOORING AS REQUIRED FOR EXTERIOR FINISHES. PROVIDE ALL FLOORING AS REQUIRED FOR INTERIOR FINISHES.
10. COORDINATE WITH MECHANICAL AND ELECTRICAL DRAWINGS FOR ALL MECHANICAL AND ELECTRICAL PENETRATIONS.
11. ALL BALCONY CEMENTS TO BE CONSTRUCTED AS PER DRAWINGS. PROVIDE ADDITIONAL BARS IN ALL PATIO SPACES.
12. AT ALL EXIST. PRESERVATION DRAFTING COUSERS, NO ADDITIONAL BARS TO BE ALLOWED TO PROTECT EXISTING REINFORCING.
13. ELEVATOR.
14. ELEVATOR BAY OVERSIGHT PROVIDED BY THE ARCHITECT. PROVIDE A COOPERATIVE WORKING AGREEMENT WITH THE ELEVATOR MANUFACTURER (SEE DRAWINGS).
15. ELEVATOR PIT SHALL BE CO-ORDINATED WITH SCHEDULING.
16. ELEVATOR PIT SHALL BE CONSTRUCTED AS PER DRAWINGS.
17. AN EMPLOYED FIBER STEEL MATERIAL, TO BE USED INSTEAD OF CONCRETE FOR THE EXTERIOR WALLS OF THE ELEVATOR PIT.
18. E. ELEVATOR PIT SHALL BE CONSTRUCTED TO ALLOW SIDEWALK GENERAL CONTRACTOR.
19. LOCKER AREA.
20. LOCKER AREA SHALL BE 10' X 10' MINIMUM (1' LOCKER AREA PER PERSON). PROVIDE 1/2" THICK POLYURETHANE INSULATED ALUMINUM PANEL SPRINGLOADED DEFLECTED THROUGH THE DOOR.
21. REVIEW LOCKER DRAWINGS PREPARED BY ARCHITECT. PROVIDE LOCKER AREA PER PERSON DRAWING.
22. HYDRAULIC SYSTEM TO COMPLY WITH TORONTO CITY BYLAW. PROVIDE 4000 X 3000 X 100" HYDRAULIC CYLINDER.

[illegible][illegible]

10. *Journal of the American Medical Association*, 2000; 284: 1039-1044.

Journal of Management Education 36(7) 809–826

[illegible]

10. *Journal of the American Medical Association*, 2000; 284: 1039-1044.

[illegible]

Journal of Management Education 36(7)p. 809-824

10. *Journal of the American Medical Association*, 2000; 284: 1039-1044.

Journal of Management Education 36(7)p. 809-824

10. *Journal of the American Medical Association*, 2000; 284: 1039-1044.

Journal of Management Education 36(7)p. 809-824

General Typical F
