



	DENOTES FIRE HOSE CABINET HOSE LENGTH 30m = 3m HOSE STREAM.
	DENOTES TRAVEL DISTANCE 45m MAXIMUM.
	DENOTES DEAD END CORRIDORS 6m MAXIMUM.

GENERAL TYPICAL FLOOR NOTES

10. PROVIDE WIRE MESH DOOR AND CEILING. ALL WIRE MESH CEILING
TO BE 45mm (1 7/8") SPACING (OR THROUGHOUT).
- REVIEW LOCKER ROOM LAYOUT PREPARED BY ARCHITECT AND INSTALLER
TO PROVIDE. INSTALL SHOWER DRAIN FOR REVIEW BY OWNER AND
ARCHITECT.
11. BICYCLE SPACE NOTES:
ALL BICYCLE SPACES TO COMPLY WITH TORONTO BICYCLE BYLAW STANDARDS
HORIZONTAL RACKING: 600 x 1300px x 190px.
VERTICAL RACKING: 600 x 1300px x 190px.
12. ADJUST REINFORCED CONCRETE TO BE ON ALL SITES (A/FORDABLE LOBBY
AND CORRIDOR WALLS).
13. SUITE TO SUITE BLOCK WALL TO BE NORMAL HEIGHT FOR ACCOUTRICS
REFER TO ACCOUTRICS REPORT

Downloaded from ascelibrary.org by University of California, San Diego on 06/01/14. Copyright ASCE, For All Rights Reserved, No part of this document may be reproduced without written permission from ASCE.