



1. ASSUME TOP OF FLOOR SLAB ELEVATION IS 40.000.
FOR FLOOR SLAB ELEVATION SEE BUILDING SECTION DRAWINGS.
2. CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR TO
CONSTRUCT 15" WITH GRID LINE, UNLESS NOTED OTHERWISE.
3. REFER TO STRUCTURAL DRAWINGS FOR FURTHER
DETAILS, MATERIALS, AND BRAND DESIGNATIONS.
4. REFER TO ELECTRICAL SHAFT SIZE AND OPENINGS REFER TO
ELECTRICAL DRAWINGS.
5. CONTRACTORS TO CONFORM TO STATE LAWS WITH
PRECEDENT BARS MANUFACTURED, FOR FARM ROAD
LANDING FROM STATION SECTION ON A - SERIES DRAWINGS.
6. CONTRACTORS TO CONFORM TO STATE LAWS WITH
PRECEDENT BARS MANUFACTURED, FOR FARM ROAD
LANDING REFER TO STATION SECTION ON A - SERIES DRAWINGS.
7. REFER TO LANDSCAPE DRAWINGS FOR PLANTER WALL
DETAILS, MATERIALS, AND BRAND DESIGNATIONS
AND GENERAL DETAILS AND DIMENSIONS.
8. PROVIDE 12" MINIMUM CONCRETE THICKNESS FOR
HORIZONTAL SHAFT OPENINGS SIZE 8 IN WALLS
OVER 12" MINIMUM CONCRETE THICKNESS FOR
VERTICAL SHAFT OPENINGS SIZE 8 IN WALLS
AND FOR ROUND OPENINGS SIZE
8 IN WALLS.
9. REFER TO KIDMAN DRAWINGS FOR SUBMITTAL LOCATIONS.
CONTRACTOR SHALL PROVIDE ALL MATERIALS AND LABOR WHICH
ARE TO BE COMPLETED BY THE SUBMITTOR'S SITE.
10. REFER TO SHEDWOOD GEOTECHNICAL ENGINEERING DRAWINGS
FOR FOUNDATION SHORING AND BRACE DETAILS FOR
CONSTRUCTION.
11. DRAWINGS FOR CRANE FOWER LOCATIONS AND CRANE
TRAILERS ARE ONLY PROVIDED AND ARE TO BE COORDINATE
WITH THE SHEDWOOD GEOTECHNICAL ENGINEERING
DRAWINGS.

General Slab Edge Notes 2
A9-30

- | | |
|-----------|---|
| | DARK HATCH INDICATES CONCRETE WALL OR COLUMN |
| | LIGHT HATCH INDICATES STRUCTURAL WALL, LOSS WALL, OR HANGERS |
| | LIGHTER HATCH INDICATES STRUCTURAL TRANSFER BEAMS, BALCONIES, OR TERRACES |
| | DARKER HATCH INDICATES CONCRETE TOPPING |
| | WATERED AREA INDICATES SECONDARY CONCRETE POUR |
| | DARKER AREA INDICATES FLOORED SLAB |
| ✓ | EXISTING FINISHED LANDSCAPE GRADING, REFER TO LANDSCAPE DRAWING |
| 1.0.0.0.0 | TOP OF CONCRETE SLAB HIGH POINT |
| 1.0.0.0.0 | TOP OF CONCRETE SLAB LOW POINT |
| 1.0.0.0.0 | TOP OF CONCRETE BEAM |
| 1.0.0.0.0 | TOP OF CONCRETE CURB |
| 1.0.0.0.0 | TOP OF CONCRETE FOUNDATION WALL |
| 1.0.0.0.0 | TOP OF FOOTING |
| 1.0.0.0.0 | TOP OF CONCRETE HATCH |
| 1.0.0.0.0 | TOP OF CONCRETE SLAB |
| 1.0.0.0.0 | TOP OF SECONDARY POUR |
| 1.0.0.0.0 | TOP OF CONCRETE LEDGE |
| 1.0.0.0.0 | TOP OF CONCRETE SLAB DEPRESSION |
| 1.0.0.0.0 | TOP OF CONCRETE UPLIFT/BEAM |
| 1.0.0.0.0 | TOP OF CONCRETE WALL |
| 1.0.0.0.0 | TOP OF CONCRETE FLOATING SLAB |
| 1.0.0.0.0 | TOP OF CONCRETE FLOATING CURB |
| 1.0.0.0.0 | TOP OF CONCRETE PAVEMENT |
| 1.0.0.0.0 | TOP OF CONCRETE TOPPING |
| 1.0.0.0.0 | TOP OF CONCRETE TOPPING HIGH POINT |
| 1.0.0.0.0 | TOP OF CONCRETE TOPPING LOW POINT |
| 1.0.0.0.0 | TOP OF CONCRETE LANDSCAPE CURB (ALSO REFER TO LANDSCAPE DRAWINGS) |
| 1.0.0.0.0 | UNDERSIDE OF CONCRETE BEAM |
| 1.0.0.0.0 | TOP OF STRUCTURAL TIE |
| 1.0.0.0.0 | TOP OF CONCRETE MUD SLAB |