

- | | |
|----|--|
| 2 | ASSUME TOP OF FLOOR SLAB ELEVATION AS ±0.000.
FOR FLOOR SLAB ELEVATION SEE BUILDING SECTION DRAWINGS |
| 3 | ALL STRUCTURE COLLINGS AND STEEL WALLS ARE
LOCATED WITH GREY SHADING IN THE DRAWINGS |
| 4 | REFER TO STRUCTURAL DRAWINGS FOR FURTHER
DETAILS OF STEEL BEAMS AND WALLS |
| 5 | FOR ELEVATOR SHAFT SEE AND OPENINGS REFER TO
SHOP DRAWINGS FOR DETAILS |
| 6 | CONTRACTORS TO CONFIRM START LOCATION WITH
LOCAL CEMENT MANUFACTURE |
| 7 | FOR ELEVATOR SHAFT SEE AND OPENINGS REFER TO
LANDING REFER TO START SECTION ON A - SERIES DRAWINGS |
| 8 | CONTRACTORS TO CONFIRM START LOCATION WITH
LOCAL CEMENT MANUFACTURE |
| 9 | FOR ELEVATOR SHAFT SEE AND OPENINGS REFER TO
LANDING REFER TO START SECTION ON A - SERIES DRAWINGS |
| 10 | REFER TO LANDSCAPE DRAWINGS FOR PLANTER WALL
DETAILS AND GENERAL DETAIL FOR WALL LOCATIONS
AND GENERAL DETAILS AND DIMENSIONS |
| 11 | REFER TO MECHANICAL AND ELECTRICAL DRAWINGS FOR
FORCED AIR SYSTEM OPENING LOCATIONS IN FLOORS
AND WALLS. FOR MECHANICAL AND ELECTRICAL
LOADS AND FOR AIR-SEAL OPENING LOCATIONS |
| 12 | REFER TO ROOMS DRAWINGS FOR SUBMITTED LOCATIONS,
ORIENTATIONS AND COORDINATES OF PROPERTY LINES WHICH
WILL BE THE PROPERTY OF THE PROJECT |
| 13 | REFER TO SITEWORK GEOSTRUCTURAL ENGINEERING DRAWINGS
FOR EXCAVATION SHORINGS AND TEMPORARY SHORING FOR
CONCRETE |
| 14 | DIMENSIONS FOR CRANE TOWER LOCATIONS AND CRANE TOWER
SLAB OPENING ARE CRANE POWERED LOCATIONS AND ARE TO BE COORDINATED
WITH CRANE MANUFACTURER |

A9-36

 DARK HATCH INDICATES CONCRETE WALL OR COLUMN
 LIGHT HATCH INDICATES STRUCTURAL CURBS, LOW WALLS, OR HAUNCHES
 LIGHTER HATCH INDICATES STRUCTURAL TRANSFER SLABS, BALCONY'S, OR TERRACES
 HATCHED AREA INDICATES CONCRETE TOPPING
 HATCHED AREA INDICATES SECONDARY CONCRETE POUR
 HATCHED AREA INDICATES FLOATING SLAB

- _____

Score _____

A9-36