DOOR AND FRAME SCHEDULE – LEVEL P4

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
P403		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	
P404		**990**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	
P412		965	2150	45	A1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	
P413		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	
P414		**940**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**

DOOR AND FRAME SCHEDULE – LEVEL P3

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
P301		**990**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**
P302		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	
P308		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	
P309		**940**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**

DOOR AND FRAME SCHEDULE – LEVEL P2

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
P214		**940**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**
P215		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	

DOOR AND FRAME SCHEDULE – LEVEL P1

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
P108A		965	2150	45	B1	HM	PT.14	F1	HM	PT.14	90 MIN.	2 HR.	–	■	■	■	–	■	■	–	REFER TO SCREEN ELEVATIONS ON A8-06, FIRELITE GLASS
P106		965	2188	45	C1	HM/GL	PT.14	F1	HM	PT.14	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	POWER OPERATED
P105		965	2440	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P107A		–	–	**45**	**C1**	**WD**	**WD.3**	**F3**	–	–	–	–	–	–	■	–	–	■	■	–	**CONCEALED WILLMORK DOOR. REFER TO ELEVATION 2/D8.2 FOR DIMENSIONS/FINISHES/HARDWARE**
P108	2x	810	2135	45	G2	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	■	■	–	
P109		810	2135	45	G1	WD	PT.21	F3	WD	PT.21	–	–	–	–	■	–	–	■	■	–	
P110		965	2135	45	G1	WD	PT.16/PT.2	F3	WD	PT.16/PT.2	–	–	–	–	■	■	–	■	■	–	SOLID CORE ACOUSTICAL DOOR, POWER OPERATED, PT.16 FOR AMENITY CORRIDOR SIDE
P111		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P111A		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P112A		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	–	–	–	–	–	■	
P112B		810	2135	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	■	
P112C		965	2135	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	■	
P120		965	2135	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P113		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P114		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P114A		710	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	–	–	–	–	–	■	
P114B		965	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	–	–	–	–	–	■	
P114C		810	2135	25	U1	GL	–	–	–	–	–	–	–	–	–	–	–	–	–	■	
P114D		965	2135	25	U1	GL	–	–	–	–	–	–	–	–	–	–	–	–	–	■	
P114E		965	2135	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P115		965	2440	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P116		965	2440	25	U1	GL	–	–	–	–	–	–	–	–	■	–	–	■	■	–	POWER OPERATED
P117		940	2188	45	C1	HM/GL	PT.14	F1	HM	PT.14	90 MIN.	2 HR.	–	–	■	■	■	■	■	–	REFER TO SCREEN ELEVATIONS ON A8-06, FIRELITE GLASS
8 **P118**		**940**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**
~~**P119A**~~		~~**940**~~	~~**2188**~~	~~**45**~~	~~**C1**~~	~~**AL/GL**~~	~~**ANOD**~~	~~**F2**~~	~~**AL**~~	~~**ANOD**~~	~~–~~	~~–~~	~~–~~	~~–~~	~~■~~	~~■~~	~~■~~	~~■~~	~~■~~	~~–~~	~~**REFER TO SCREEN ELEVATIONS ON A8-06**~~
P129		**940**	**2188**	**45**	**C1**	**AL/GL**	**ANOD**	**F2**	**AL**	**ANOD**	–	–	–	–	■	■	■	■	■	–	**REFER TO SCREEN ELEVATIONS ON A8-06**
P130		965	2150	45	B1	HM	PT.12	F1	HM	PT.12	90 MIN.	2 HR.	–	–	■	–	–	■	■	–	

DOOR AND FRAME SCHEDULE – LEVEL 1

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
105		915	2135	45	G1	WD	WD.3/PT.11	F3	WD	WD.3/PT.11	–	–	–	–	■	–	–	–	–	■	WD.3 FOR LOBBY SIDE, PT.15 FOR STAFF W/C SIDE
106		965	2135	45	G1	WD	PT.14/PT.15	F3	WD	PT.14/PT.15	–	–	–	–	■	–	–	–	–	■	POWER OPERATED, PT.14 FOR LOBBY SIDE, PT.15 FOR W/C SIDE
107		965	2135	45	G1	WD	PT.14/PT.8	F3	WD	PT.14/PT.8	–	–	–	–	■	–	–	–	–	■	PT.14 FOR LOBBY SIDE, PT.8 FOR ADMIN OFFICE SIDE
107A	2x	710	2135	45	G2	WD	PT.8	F3	WD	PT.8	–	–	–	–	–	–	–	–	–	–	
109		965	2135	45	G1	WD	PT.16/PT.8	F3	WD	PT.16/PT.8	–	–	–	–	■	–	–	–	–	–	POWER OPERATED, PT.16 FOR MAIL PICK-UP SIDE, PT.8 FOR MEETING ROOM SIDE
110		965	2135	45	G1	WD	PT.8	F3	WD	PT.8	–	–	–	–	■	–	–	–	–	–	
111		965	2135	45	G1	WD	PT.8	F3	WD	PT.8	–	–	–	–	■	–	–	–	–	–	
112		915	2150	45	B1	HM	PT.16	F1	HM	PT.16	90 MIN.	2 HR.	–	–	■	–	–	–	–	–	
113		965	2135	45	G1	WD	PT.16/PT.15	F3	WD	PT.16/PT.15	–	–	–	–	■	–	–	–	–	■	POWER OPERATED, PT.16 FOR LOBBY SIDE, PT.15 FOR W/C SIDE
114		915	2135	45	G1	WD	PT.16/PT.8	F3	WD	PT.16/PT.8	–	–	–	–	■	–	–	–	–	■	PT.16 FOR LOBBY SIDE, PT.8 FOR STAFF ROOM SIDE
116		965	2135	45	G1	WD	PT.14/PT.8	F3	WD	PT.14/PT.8	–	–	–	–	■	–	–	–	–	■	PT.14 FOR LOBBY SIDE, PT.8 FOR PARCEL ROOM SIDE
117		915	2135	45	G1	WD	PT.14	F3	WD	PT.14	–	–	–	–	■	–	–	–	–	■	
118		915	2150	45	A1	HM	PT.14	F1	HM	PT.14	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
139		915	2135	45	A1	HM	PT.16	F1	HM	PT.16	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
141		915	2135	45	G1	WD	PT.16	F3	WD	PT.16	–	–	–	–	■	–	–	–	–	■	

DOOR AND FRAME SCHEDULE – LEVEL 2

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
202		965	2135	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	■	■	■	–	■	–	–	HOLD OPEN, WD.2 FOR DOOR/FRAME BOTH SIDES, PT.20 WHERE METAL FRAME MAY BE EXPOSED
203		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
204	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
205	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	■	■	–	–	–	–	■	
206		915	2135	45	C1	WD	PT.18	F5	MTL	PT.18	20 MIN.	1 HR.	–	■	■	–	–	–	–	■	
207		965	2135	45	G1	WD	PT.18/PT.15	F5	MTL	PT.18/PT.15	20 MIN.	1 HR.	–	–	■	–	–	–	–	■	POWER OPERATED, PT.18 FOR CORRIDOR SIDE, PT.15 FOR W/C SIDE
208		915	2135	45	G1	WD	PT.19/PT.15	F3	WD	PT.19/PT.15	–	–	–	–	■	–	–	–	–	■	PT.19 FOR BILLIARDS ROOM SIDE, PT.15 FOR W/C SIDE
209		915	2440	45	J1	WD	WD.6	–	–	–	–	–	–	–	■	–	–	–	–	–	
212	2x	965	2440	25	U2	GL	–	–	–	–	–	–	–	–	■	–	–	–	–	■	POWER OPERATED ONE SIDE
212A		1270	2440	45	J1	WD	WD.6	–	–	–	–	–	–	–	■	–	–	–	–	–	
214	2x	965	2440	25	U2	GL	–	–	–	–	–	–	–	–	■	–	–	–	–	■	POWER OPERATED ONE SIDE
216		915	2135	45	C1	WD	PT.17/PT.15	F3	WD	PT.17/PT.15	–	–	–	–	■	–	–	–	–	■	PT.17 FOR CORRIDOR SIDE, PT.15 FOR CATERING KITCHEN SIDE
216A		915	2135	45	G1	WD	WD.6/PT.15	F3	WD	WD.6/PT.15	–	–	–	–	■	–	–	–	–	–	WD.6 FOR DINING AREA SIDE, PT.15 FOR CATERING KITCHEN SIDE
216B	**2x**		**2135**	**45**		**WD.7**				**WD.7**											
217		915	2135	45	G1	WD	PT.17	F3	WD	PT.17	–	–	–	–	■	–	–	–	–	■	CAN DOOR SWING OUT INSTEAD OF IN?
218		965	2135	45	G1	WD	PT.17/PT.15	F3	WD	PT.17/PT.15	–	–	–	–	■	–	–	–	–	■	POWER OPERATED, PT.17 FOR CORRIDOR SIDE, PT.15 FOR W/C SIDE
219		915	2135	45	G1	WD	PT.17/PT.15	F3	WD	PT.17/PT.15	–	–	–	–	■	–	–	–	–	■	PT.17 FOR CORRIDOR SIDE, PT.15 FOR W/C SIDE
220		965	2135	45	G1	WD	WD.2	F5	MTL	WD.2/PT.20	20 MIN.	1 HR.	–	■	–	–	–	–	–	–	HOLD OPEN, WD.2 FOR DOOR/FRAME BOTH SIDES, PT.20 WHERE METAL FRAME MAY BE EXPOSED
221	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
222		915	2135	45	G1	WD	PT.18	F5	MTL	PT.18	20 MIN.	1 HR.	–	■	–	–	–	–	–	■	
225		965	2135	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	■	
226		915	2150	45	A1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
227		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
227A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, SECURITY
G-2		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
H-2		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-2		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 3

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
303		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	■	■	■	–	■	–	–	
304	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
305	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
306	2x	510	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
310		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	■	–	–	–	■	–	–	
311		915	2150	45	A1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
312		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	MAG LOCK
312A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, MAG LOCK
G-3		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	MAG LOCK
H-3		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-3		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 4

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
403		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	■	■	■	–	■	–	–	
404	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
405	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
406	2x	510	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
410		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	–	–	■	–	–	
411		915	2150	45	A1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
412		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
412A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, SECURITY
G-4		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
H-4		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-4		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 5

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
503		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
504	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
505	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
506	2x	510	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
512		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	–	–	■	–	–	
511		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
512		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
512A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, SECURITY
G-5		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	■	SECURITY
H-5		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-5		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 6

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
603		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
604	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
605	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
606	2x	510	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
610		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
611		915	2150	45	A1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
612		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	SECURITY
612A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, SECURITY
G-6		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	■	SECURITY
H-6		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-6		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 7

DOOR NUMBER	NUMBER OF DOOR PANELS	WIDTH	HEIGHT	THICKNESS	DOOR TYPE	DOOR PANEL MATERIAL	DOOR PANEL FINISH	FRAME TYPE	FRAME MATERIAL	FRAME FINISH	FIRE RATING (DOOR)	FIRE RATING (WALL)	TEMPERATURE RISE LABEL	PANIC HARDWARE	SELF CLOSURE	THRESHOLD	INSULATED	WEATHER STRIPPING	AUTO OPEN	LOCK HARDWARE	COMMENTS
703		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
704	2x	710	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
705	2x	610	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
706	2x	510	2150	45	A2	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
710		965	2150	45	A1	HM	PT.18	F1	HM	PT.18	45 MIN.	1 HR.	–	–	■	■	–	■	–	–	
711		915	2150	45	A1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	
712		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	MAG LOCK
712A		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	–	–	–	–	■	REFER TO ARTSCAPE ID DRAWINGS FOR FINISHES, MAG LOCK
G-7		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	MAG LOCK
H-7		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	
K-7		915	2150	45	B1	HM	PT.18	F1	HM	PT.18	90 MIN.	2 HR.	–	–	■	■	–	■	–	–	

DOOR AND FRAME SCHEDULE – LEVEL 8

| DOOR NUMBER | NUMBER OF DOOR PANELS | WIDTH | HEIGHT | THICKNESS | DOOR TYPE | DOOR PANEL MATERIAL | DOOR PANEL FINISH | FRAME TYPE | FRAME MATERIAL | FRAME FINISH | FIRE RATING (DOOR) | FIRE RATING (WALL) | TEMPERATURE RISE LABEL | PANIC HARDWARE | SELF CLOSURE | THRESHOLD | INSULATED | WEATHER STRIPPING | AUTO OPEN | LOCK HARDWARE | COM